

### Standard Technical Data for the Horizontal Sliding Mezzanine Gate

1. Mezzanine Gate Operation to be one of the following;
  - a. Manual.
  - b. Electric; Electric drive system, 115 VAC, (24 VDC Secondary), 60 HZ, 1/3 HP. Operator control panel includes timer-to-close capability, obstruction sensing and one (1) three-button (Open-Stop-Close) control panel mounted push button station, and one (1) remotely located wall mount secondary 3-button push button. Includes Amber color WARNING strobe light, activates when gate is in operation.
2. Mounting Location on mezzanine to be one of the following;
  - a. Deck Mount
  - b. Face Mount
3. Gate Section; to be factory welded frame work with horizontal top rail. Includes mid-rail, 4" high toe board, 42" overall height, and vertical members not to exceed 8' on center. Gate shall meet or exceed Federal OSHA standard for standard railings at the time of manufacture relative to dimensions and loading. To be fabricated from one of the following;
  - a. Mild Steel
  - b. 304-2b Stainless Steel
  - c. 316L Stainless Steel
4. Rollers to be minimum 2-5/8" diameter, concealed within toe board. Rollers to be non-corrosive.
5. Slide Direction; slide left or slide right (determined which way gate will slide open when looking up at it from the ground floor).
6. Track, guides, brackets and mounts to be furnished in accordance with dimensional requirement of gate in lengths and sizes appropriate for handling and shipping.
5. Finish to be;
  - a. Mild steel mezzanine gates; exposed surfaces to be Powder Coat Safety Yellow. Hardware/fasteners to be zinc plated.
  - b. Stainless steel mezzanine gates (304-2b or 316L); mill finish, acid washed. Interfering welds ground smooth, not polished. Hardware/fasteners to be stainless steel.
6. Warranty to be One (1) Year from date of shipment, finish excluded.
7. Available Options:
  - a. Remote controls; gate systems with electric controls only.
  - b. Photoeyes; gate systems with electrical controls only
  - c. Pull cord switch; gate systems with electric or pneumatic controls only.

**Exclusions:**

1. All electrical wiring or airline piping to and between all components by others.
2. Structural Review of mezzanine to accept loading and anchor design by others.

NAME	ADDRESS	PHONE
COMPANY	CITY, ST, ZIP	EMAIL



1150 S. 48TH STREET, GRAND FORKS, ND 58201  
PHONE 701.746.4519 TOLL FREE 877.446.1519  
FAX 701.746.8340 WWW.PSDOORS.COM


# CUT-SHEET: HORIZONTAL MEZZANINE GATE; MODEL MGH

Quantity: \_\_\_\_\_

<input checked="" type="checkbox"/>	<b>ID</b>	<b>Operation<sup>1</sup></b>
<input type="checkbox"/>	M	Manual
<input type="checkbox"/>	E	Electric
<input checked="" type="checkbox"/>	<b>ID</b>	<b>Mounting Location (See Detail C)</b>
<input type="checkbox"/>	D	Deck Mount
<input type="checkbox"/>	F	Face Mount
<input checked="" type="checkbox"/>	<b>ID</b>	<b>Material/Finish</b>
<input type="checkbox"/>	M	Mild Steel (Powder Coat Safety Yellow)
<input type="checkbox"/>	S	304 Stainless Steel (Unfinished/Mill)
<input type="checkbox"/>	L	316L Stainless Steel (Unfinished/Mill)
<input checked="" type="checkbox"/>	<b>Slide Direction (As viewed from floor below)</b>	
<input type="checkbox"/>	L	Left
<input type="checkbox"/>	R	Right
<input checked="" type="checkbox"/>	<b>ID</b>	<b>Nominal Opening Width</b>
<input type="checkbox"/>	048	4' (48")
<input type="checkbox"/>	<b>072</b>	<b>6' (72") - STOCK SIZE<sup>2</sup></b>
<input type="checkbox"/>	<b>096</b>	<b>8' (96") - STOCK SIZE<sup>2</sup></b>
<input type="checkbox"/>	120	10' (120")
<input type="checkbox"/>	144	12' (144")
<input type="checkbox"/>	168	14' (168")
<input type="checkbox"/>	192	16' (192")
<input type="checkbox"/>	###	Custom _____ (inches)
<input checked="" type="checkbox"/>	<b>ID</b>	<b>OPTIONS<sup>1</sup> (Electric Controls Only)</b>
<input type="checkbox"/>	511322	Radio Control Kit; Keypad
<input type="checkbox"/>	502918	Add'l Transmitter; Keypad Qty: _____
<input type="checkbox"/>	501715	Switch; Ceiling Pull Cord
<input type="checkbox"/>	511756	Photoeye Kit (Electric)

**NOTES:**

- <sup>1</sup> See product Technical Data for details.
- <sup>2</sup> Stock Gates are Mild Steel with Powder Coat Yellow Finish.



NAME	ADDRESS	PHONE
COMPANY	CITY, ST, ZIP	EMAIL

**PS DOORS** 1150 S. 48TH STREET, GRAND FORKS, ND 58201  
 MANUFACTURING DIVISION PHONE 701.746.4519 TOLL FREE 877.446.1519  
 FAX 701.746.8340 WWW.PSDOORS.COM